



Mini UFO LED High Bay Light

Features

- Mini UFO LED high bay light with compact design
- Microwave sensor optional for more energy saved
- Opal PC cover optional for smooth light & glare control
- Superior electrical and thermal conductivity
- Lumileds/Samsung/Osram SMD LED with LM80 report
- Overall luminous efficacy up to 150LPW
- MEANWELL or CE/TUV/UL approved driver optional
- Triac, 0-10V & DALI dimming optional



Applications

- Suitable for wet location optional
- Warehouse and industrial lighting



Specifications (standard)



Item No.	Wattage (W)	Voltage (V)	Luminous Flux	CCT (K)	CRI (Ra)	Beam Angle	PF	Dimensions (mm)	IP Rating
SO-UFO-M100W	100W	AC100-277V	15000lm	2700-6500K	80	60/90/110°	>0.9	Ø250xH178mm	IP65
SO-UFO-M150W	150W	AC100-277V	22500lm	2700-6500K	80	60/90/110°	>0.9	Ø230xH180mm	IP65
SO-UFO-M200W	200W	AC100-277V	30000lm	2700-6500K	80	60/90/110°	>0.9	Ø345xH183mm	IP65

Specifications (sensor)

Item No.	Wattage (W)	Voltage (V)	Luminous Flux	CCT (K)	CRI (Ra)	Beam Angle	PF	Dimensions (mm)	IP Rating
SO-UFO-MS100W	100W	AC100-277V	15000lm	2700-6500K	80	60/90/110°	>0.9	Ø250xH178mm	IP65
SO-UFO-MS150W	150W	AC100-277V	22500lm	2700-6500K	80	60/90/110°	>0.9	Ø230xH180mm	IP65
SO-UFO-MS200W	200W	AC100-277V	30000lm	2700-6500K	80	60/90/110°	>0.9	Ø345xH183mm	IP65

