



Features

- Modular design LED outdoor light with DIY capability
- Aluminum alloy heatsink for best heat dissipation
- Used as flood light, tunnel light, low bay light, area light
- Heavy duty trunnion bracket with 180° adjustable
- Meanwell driver plus Lumileds LED with quality assurance
- Various beam angle options: 60x60°/90x90°/60x150°
- Modular design with max wattage up to 300W



Specifications



Item No.	Wattage (W)	Voltage (V)	Luminous Flux	CCT (K)	CRI (Ra)	Beam Angle	PF	Dimensions (mm)	IP Rating
SO-FLD-50W	50W	AC100-277V	6000lm	2700-6500K	70	60x60°/90x90°/60°x150°	>0.9	L193xW315xH130	IP65
SO-FLD-100W	100W	AC100-277V	12000lm	2700-6500K	70	60x60°/90x90°/60°x150°	>0.9	L238xW315xH130	IP65
SO-FLD-150W	150W	AC100-277V	18000lm	2700-6500K	70	60x60°/90x90°/60°x150°	>0.9	L283xW315xH130	IP65
SO-FLD-200W	200W	AC100-277V	24000lm	2700-6500K	70	60x60°/90x90°/60°x150°	>0.9	L373xW315xH130	IP65
SO-FLD-300W	300W	AC100-277V	36000lm	2700-6500K	70	60x60°/90x90°/60°x150°	>0.9	L283xW599xH130	IP65

