

# LED TRIPROOF LIGHT



# Classic T Series



## LED Tri-proof Light **Classic T Series**

### Features

- Polycarbonate base & cover, impact resistant & high transmittance
- Classic version tri-proof light with LED source inside, more traditional
- High luminous flux SMD LED with LM80 report
- Overall luminous efficacy from 120-140LPW
- Non-flicker LED driver with UL/TUV/SAA/CE certified
- Surface mount & suspended installation optional
- Stainless steel buckles and brackets for strong connector
- Dimmable / Microwave Sensor / Emergency available



### Specifications



Item No.	Wattage (W)	Voltage (V)	Luminous Flux	CCT (K)	CRI (Ra)	Beam Angle	PF	Dimensions (mm)	IP
SO-TPL-06TA20W	20W	AC200-240V	2400lm	2700-6500K	>80	120°	>0.9	L600xW95xH80	IP65
SO-TPL-12TA40W	40W	AC200-240V	4800lm	2700-6500K	>80	120°	>0.9	L1200xW95xH80	IP65
SO-TPL-15TA50W	50W	AC200-240V	6000lm	2700-6500K	>80	120°	>0.9	L1500xW95xH80	IP65
SO-TPL-06TB30W	30W	AC200-240V	3600lm	2700-6500K	>80	120°	>0.9	L600xW125xH88	IP65
SO-TPL-12TB40W	40W	AC200-240V	4800lm	2700-6500K	>80	120°	>0.9	L1200xW125xH88	IP65
SO-TPL-12TB50W	50W	AC200-240V	6000lm	2700-6500K	>80	120°	>0.9	L1200xW125xH88	IP65
SO-TPL-12TB60W	60W	AC200-240V	7200lm	2700-6500K	>80	120°	>0.9	L1200xW125xH88	IP65
SO-TPL-15TB60W	60W	AC200-240V	7200lm	2700-6500K	>80	120°	>0.9	L1500xW125xH88	IP65
SO-TPL-15TB80W	80W	AC200-240V	9600lm	2700-6500K	>80	120°	>0.9	L1500xW125xH88	IP65

